



Self-priming Chemical FRPP Pumps

PD

Features:

- Tough construction against high corrosive and high temperature chemical liquids by adopting self-cooling design " **TEFLON BELLOW SEAL** "
- Power: 1, 2, 3, 5 HP
- Frequency: 50/60HZ
- Motor: 2 Poles
- Agency Listing: CE, CSA, C-US Mark
- Maximum Permissible Temperature: 70 °C



50 Hz Specification: 2950 RPM

Type	S.G.	Motor				Pump				Wt.	Height.	Pump Dia.
		Power		Phase	Volt	Bore Size		Max. Head	Max. Flow			
		HP	kW	PH	V	Inlet Inch (mm)	Outlet inch (mm)	m	m ³ /min			
PD-132	1.0	1	0.75	3	380 ~ 460	1.5"(40)	1.5"(40)	12	0.2	26	374	625
PD-232	1.0	2	1.5	3	380 ~ 460	1.5"(40)	1.5"(40)	18	0.36	34	374	704
PD-332	1.0	3	2.2	3	380 ~ 460	2" (50)	2" (50)	21	0.5	42	374	704
PD-532	1.0	5	3.7	3	380 ~ 460	2" (50)	2" (50)	26	0.48	56	420	780
PD-532L	1.0	5	3.7	3	380 ~ 460	3" (80)	3" (80)	24	0.68	68	425	830

60 Hz Specification: 3450 RPM

Type	S.G.	Motor				Pump				Wt.	Height.	Pump Dia.
		Power		Phase	Volt	Bore Size		Max. Head	Max. Flow			
		HP	kW	PH	V	Inlet Inch (mm)	Outlet inch (mm)	m	m ³ /min			
PD-132	1.0	1	0.75	3	220 ~ 460	1.5"(40)	1.5"(40)	10	0.19	26	374	625
PD-232	1.0	2	1.5	3	220 ~ 460	1.5"(40)	1.5"(40)	20	0.38	34	374	704
PD-332	1.0	3	2.2	3	220 ~ 460	2" (50)	2" (50)	24	0.48	42	374	704
PD-532	1.0	5	3.7	3	220 ~ 460	2" (50)	2" (50)	28	0.60	56	420	780
PD-532L	1.0	5	3.7	3	220 ~ 460	3" (80)	3" (80)	28	0.68	68	425	830